

## The HemoCue<sup>®</sup> Hb 201 DM System provides lab-quality hemoglobin results at the point-of-care

Data Management Features<sup>1</sup> Include:

- Data Entry Touch-screen display and built-in barcode scanner
- Interface Capabilities Interface with existing network using POCT1-A (CIC standard) with our DMS software. Docking solution enables connection of up to 5 analyzers.
- **Configurable Functions** Operator ID, Patient ID, Lot ID, Site ID; Patient comments; Critical value alerts; STAT Testing
- Results Storage 4,000 patient/STAT tests, 500 QC tests, 500 analyzer logs, 200 patient IDs
- DMS Software Patient and QC reports
- Quality Control Data Management QC lock-out; QC scheduling; Linearity Reports



## HemoCue OnCue<sup>™</sup> Support


HemoCue OnCue<sup>™</sup> Support is a comprehensive program designed to meet your needs as quickly and conveniently as possible.

Powered by HemoCue employees, you get answers and education from the experts who know our products best.

At your office, online, or on the phone, we're ready to do more for you.

## Product Specifications<sup>1,2</sup>

Principle	Modified azidemethemoglobin reaction; dual wavelengths (570 nm and 880 nm) for compensation of turbidity
Calibration	Factory calibrated against the ICSH reference method; needs no further calibration
Sample Material	Capillary, venous or arterial whole blood
Measurement Range	0–25.6 g/dL (0–256 g/L, 0–15.9 mmol/L)
Results	Within 60 seconds
Sample Volume	~10 µL
Dimensions	Analyzer: 6.70 x 3.66 x 1.97 inches Docking Station: 8.10 x 5.30 x 2.40 inches
Weight	Analyzer: 0.77 pounds with batteries installed Docking Station: 1.24 pounds
Storage Temperature	Analyzer: 32–122 °F (0–50 °C) Microcuvettes: unopened 59–86 °F (15–30 °C); three-month open vial stability
Operating Temperature	64-86 °F (18-30 °C)
Power Options	Internal rechargeable batteries or docking station with AC adapter
Quality Control	Built-in self-test; optional liquid controls*
СРТ	<b>85018-QW</b> The CPT codes provided are based on AMA guidelines and are for informational purposes only. CPT coding is the sole responsibility of the bill party. Please direct any questions regarding coding to the payer being billed.



Method comparison according to CLSI EP9-A. HemoCue® Hb 201<sup>+</sup> System vs ICSH, venous blood samples, g/dL.<sup>3</sup>

Product Order Number	
121135	HemoCue <sup>®</sup> Hb 201 DM Analyzer
111716	HemoCue® Hb 201 Microcuvettes (200/box)
111715	HemoCue® Hb 201 Individually Packaged Microcuvettes (100/box)
139143	HemoCue <sup>®</sup> 201 DM Primary Docking Station <sup>+</sup>
139144	HemoCue <sup>®</sup> 201 DM Secondary Docking Station <sup>+</sup>

\*Refer to your local or regulatory agency for any external control requirements
 <sup>1</sup> HemoCue® 201 DM Reference Manual; 901041 180503
 <sup>2</sup> Hb 201<sup>+</sup> Package Insert; 151712 180514
 <sup>3</sup> Method Comparison and Bias Estimation using patient samples acording to NCCLS EP-9 for
 Hb 201<sup>+</sup> versus ICSH (A<sup>540</sup>-A<sup>700</sup>), Site A-D, Multicenter Study (FRE0807/1).



HemoCue America | California, USA | Phone 800.881.1611 | Fax 800.333.7043 web@hemocue.com hemocue.us ©2020 HemoCue America. All rights reserved. MMUS-0138[4]